



TPT SERIES NEW CONSTRUCTION FITTING



The Testable Primary Termination New Construction Fitting brings both convenience and innovation for a simple and permanent installation.

INTEGRATED TEST PORT

The integrated test port eliminates the need for a separate test boot.

MISALIGNMENT FLEXIBILITY

Works with angled pipe entries up to 10° and allows for ±1" pipe misalignment.

COST EFFECTIVE

PCI's penetration fittings are the most affordable fiberglass fittings on the market, with a similar cost to rubber or plastic fittings.

PERMANENT BONDING

EP2A is used to bond fittings to fiberglass and steel. It has great gap filling properties and excellent sag resistance, making it a simple and dependable bonding solution.

LONG-TERM SOLUTION



100% fiberglass construction provides superior strength and ensures the fitting will withstand long-term exposure to all fuels, including ethanol. These can replace rubber or plastic boots.



PF-TPT-2F-32

Part No.	Install	Pipe	Length	ID	OD
PF-TPT-2F-32	Flat Wall	3" x 2" RTIIA	6"	2.4"	7"
PF-TPT-2F-43	Flat Wall	4" x 3" RTIIA	6"	3.8"	7.8"
PF-TPT-2F-64	Flat Wall	6" x 4" RTIIA	8.5"	4.8"	10"
PF-TPT-2F-L2*	Flat Wall	2" LCX	6"	2.4"	7"
PF-TPT-2F-L3*	Flat Wall	3" LCX	6"	3.8"	7.8"
PF-TPT-2F-L4*	Flat Wall	4" LCX	8.5"	4.8"	10.8"

*LCX Adapter Included



PART NUMBER LEGEND

Series	Generation	Pipe
PF: Penetration Fitting	2: 2nd Gen.	32: 3"x2" RTIIA 43: 4"x3" RTIIA 64: 6"x4" RTIIA L2: 2" LCX L3: 3" LCX L4: 4" LCX
PF	TPT	2
	F	32
Model TPT: TPT	Install F: Flat Wall	